

**CLAIMS**

I claim:

1. A portal-based appliance system for ultraviolet disinfection (UV) of interior surfaces and contents of containers, the system comprising a container having a housing with at least one portal positioned on the housing of a container for receiving UV light input into the container from a UV light source.

2. The UV system according to claim 1, wherein the portal is connectable to fiber optic transmission lines.

3. The UV system according to claim 2, wherein the portal is a fiber optic transmission line-ready portal.

4. The UV system according to claim 3, wherein the fiber optic transmission line-ready portal includes a fiber optic transmission line fastener.

5. The UV system according to claim 1, wherein the portal includes an interface device for providing protection to appliance components.

6. The UV system according to claim 5, wherein the interface device is UV-transmissive.

7. The UV system according to claim 1, wherein the container is used for animal housing.

8. The UV system according to claim 1, further including at least one portal optical component positioned between the portal opening and the interior of the appliance.

9. The UV system according to claim 8, wherein the at least one portal optical component is UV transmissive.

1 10. The UV system according to claim 8, wherein the at least one portal optical  
2 component is UV reflective.

3 11. The UV system according to claim 8, wherein the at least one portal optical  
4 component is selected from the group consisting of reflectors, shutters, lenses, splitters,  
5 focalizers, mirrors, rigid and flexible light guides, homogenizer, mixing rods, manifolds,  
6 couplers, filters, gratings, diffractors, color wheels, and combinations thereof.

7 12. The UV system according to claim 8, wherein the at least one portal optical  
8 component includes at least one photocatalyst that degrades compounds contacting the  
9 surface of the portal optic.

10 13. The UV system according to claim 12, wherein the at least one photocatalyst is  
11 selected from the group consisting of TiO<sub>2</sub>, WO<sub>2</sub>, ZnO, ZnS, SnO<sub>2</sub>, and PtTiO<sub>2</sub> and the  
12 like.

13 14. The UV system according to claim 1, wherein the container is an appliance  
14 selected from the group consisting of fluid-treatment appliances, fluid-dispensing  
15 appliances, fluid-storage appliances, fluid-manufacturing appliances, and combinations  
16 thereof.

17 15. The UV system according to claim 1, wherein the container is an individual use  
18 container.

19 16. The UV system according to claim 15, wherein the container is a beverage  
20 container.

21 17. The UV system according to claim 16, wherein the beverage container is selected  
22 from the group consisting of water, coffee, tea, milk, juice, carbonated beverage, wine,  
23 beer, and combinations thereof.

1 18. The UV system according to claim 15, wherein the container is a biological fluid  
2 container.

3 19. The UV system according to claim 18, wherein the container is used to contain  
4 blood, blood products, fermentation products, cell culture products, biotechnology  
5 products, and combinations thereof.

6 20. A portal system for ultraviolet disinfection (UV) of appliances, the system  
7 comprising at least one portal for receiving UV light input.

8 21. The UV system according to claim 20, wherein the portal is connectable to fiber  
9 optic transmission lines.

10 22. The UV system according to claim 21, wherein the portal is a fiber optic  
11 transmission line-ready portal.

12 23. The UV system according to claim 22, wherein the fiber optic transmission line-  
13 ready portal includes a fiber optic transmission line fastener.

14 24. The UV system according to claim 20, wherein the portal includes an interface  
15 device for providing protection to appliance components.

16 25. The UV system according to claim 24, wherein the interface device is UV-  
17 transmissive.

18 26. The UV system according to claim 20, further including at least one portal optical  
19 component positioned between the portal opening and the interior of the appliance.

20 27. The UV system according to claim 26, wherein the at least one portal optical  
21 component is UV transmissive.

22 28. The UV system according to claim 26, wherein the at least one portal optical  
23 component is UV reflective.

1 29. The UV system according to claim 26, wherein the at least one portal optical  
2 component is selected from the group consisting of reflectors, shutters, lenses, splitters,  
3 focalizers, mirrors, rigid and flexible light guides, homogenizer, mixing rods, manifolds,  
4 couplers, filters, gratings, diffractors, color wheels, and combinations thereof.

5 30. The UV system according to claim 26, wherein the at least one portal optical  
6 component includes at least one photocatalyst that degrades compounds contacting the  
7 surface of the portal optic.

8 31. The UV system according to claim 30, wherein the at least one photocatalyst is  
9 selected from the group consisting of TiO<sub>2</sub>, WO<sub>2</sub>, ZnO, ZnS, SnO<sub>2</sub>, and PtTiO<sub>2</sub> and the  
10 like.